Fascia Extender W-Offset 1-1/4" S.S. Ring Shank 12" On Center Through Pre-Punched Hole and Membrane Fascia Extender W-Offset Specify Length 1-1/4" S.S. Ring Shank 12" On Center Through Pre-Punched Hole and Membrane Fascia Extender Cleat (22GA Galv. Continuous Cleat) 2-1/2" Standard or Specify Length - Continuous Cleat and fasteners provided. **QUANTITIES:** - Concealed Splice Plates provided. - Splice Plate Sealant available for extra charge. Lineal Feet (10'-0" Lengths*): Outside Miters**: Optional Welded (Surcharge Applies) PRINT APPROVAL: Inside Miters**: Optional Welded (Surcharge Applies) Architect and/or Contractor shall verify all Right End Caps**: Optional Welded (Surcharge Applies) dimensions, sizes, and quantities, All products to be installed in strict accordance Left End Caps**: Optional Welded (Surcharge Applies) with Drexel's printed instructions. Splice Plate Tape Sealant: Optional Sealant (Surcharge Applies) Approved By: * Optional lengths available up to 20'-0" Date: ** Standard riveted PROJECT: ARCHITECT: \Box 24GA \Box .040" AL **ROOFING CONTRACTOR:** Other:_____ REPRESENTATIVE: Finish: Color:_____ Effective Date: 5-22-15 MANUFACTURING, INC. J.S. Drawn By: Approved By: B.P. P: 800-628-5849 E: office@garretymfg.com W: www.garretymfg.com