## .040" Aluminum 24GA Steel Gutter HD G-1 Horizontal = 210 psf G-1 Horizontal = 200 psf G-2 Vertical = 90 psf G-2 Vertical = 90 psfANSI/SPRI GD-1 CERTIFIED: G-3 Static = 290 psf G-3 Static = 280 psf Roof Membrane #10-13x1" S.S. Panhead Woodscrew 12" On Center Gutter Water Cut-Off Mastic Universal Single Ply Sealant Termination Bar #9 S.S. Washered Woodscrew 6" On Center #9 S.S. Washered Woodscrew (1) Per Bracket 7" Gutter HD AL Bracket (24" o.c. Max.) 5<u>15</u>" - Gutter Bracket and Fasteners provided. **QUANTITIES:** - Term Bar and fasteners NOT provided. Lineal Feet (10'-0" Lengths\*): Outside Miters\*\*: Optional Welded (Surcharge Applies) PRINT APPROVAL: Inside Miters\*\*: Optional Welded (Surcharge Applies) Architect and/or Contractor shall verify all Right End Caps\*\*: Optional Welded (Surcharge Applies) dimensions, sizes, and quantities, All products to be installed in strict accordance Left End Caps\*\*: Optional Welded (Surcharge Applies) with Drexel's printed instructions. Approved By: \* Optional lengths available up to 20'-0" Date: \*\* Standard riveted **PROJECT:** MATERIA ARCHITECT: ☐ 24GA ☐ .040" AL ROOFING CONTRACTOR: ☐ Other:\_\_\_\_\_ REPRESENTATIVE: Finish: Color<u>:</u>\_\_\_\_\_ 9-22-14 Effective Date: MANUFACTURING, INC. Drawn By: J.S.

P: 800-628-5849 E: office@garretymfg.com W: www.garretymfg.com

Approved By:

B.P.